
This drawing, specifications, and concepts contained here in are the sole property of Darl Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Darl Aerospace Eugene, OR.

REVISIONS										
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					

FIRST ARTICLE WEIGHT TEST



INSPECTION & TESTING PROCEDURES FOR THE RBW7105G00231-3G AW139 ENGINE SLING. THIS ASSEMBLY SHOULD BE INSPECTED BEFORE EACH USE.

REPLACE ANY ITEMS THAT ARE DAMAGED OR SUSPECTED OF DAMAGE BEFORE USING!

FIRST ARTICLE WEIGHT TEST

- 1. <u>AFTER INSPECTION</u>, PLACE SLING ASSEMBLY ON A OVERHEAD LIFTING DEVICE. ATTACH APPROPRIATE TEST WEIGHT OF 390 KG/858 LBS. AS SHOWN.
- 2. LIFT WEIGHT FOR AT LEAST 5 MINUTES, CONTINUALLY CHECKING FOR CRACKS, DEFLECTION, OR DISTORTION.
- 3. REMOVE WEIGHT AND RE-INSPECT SLING, CHECKING FOR STRESS CRACKS, BENDING, OR DISTORTIONS.

INSPECTOR_	
TESTER	
S.N	
DATE	

DART											
TITLE	AW139 ENGINE SLING										
DWG NO.	RBV	/710	G00231-3G		10						
MAT'L HEAT TREAT FINISH SPEC	HEAT TREAT FINISH				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125/ 1. BREAK ALL SHARP EDGES						
DRAWN BY: CHECKED: OPPS APPR:	HECKED: SM 06/01/2017 PPS APPR: AA 06/05/2017 A APPR: JL 06/13/2017			.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 USED ON MODEL AW139							
QA APPR: APPROVED:											
SCALE .	1:10	DATE	6/	1/2017	SHEET 1 OF	1					